

Generating Set

TECHNICAL DATA SHEET

SGT450



Prime Power*	Standby Power**	Voltage/Ph	Hz/rpm***	PF
400kVA/320 kWe	450kVA/360 kWe	400/3Ph	50/1500	0.8

Prime power*

Unlimited hours usage with an average load factor of 80% of the published Prime power over each 24 hours period. A 10% overload is available for 1 hour in every 12 hours operation.

Standby power**

Limited to 500 hours annual usage with an average load factor of 80% of the published Standby power rating over each 24 hour period. Up to 300 hours of annual usage may be run continuously. No overload is permitted on Standby power. Available in 60HZ for all voltage ratings.***

Standard Reference Conditions

Note: Standard reference conditions 40°C (104°F) Air Inlet Temp, 100m (328 ft) A.S.L. 30% relative humidity.

Diesel Generator Set

Engine Make /Model	PERKINS 2206A-E13TAG3
Alternator Make /Model	Leroy Somer TAL-047-A
Control Panel	DSE 6120
Base Frame / Silent Canopy	Robust Structure/ Corrosion Resistant
Circuit Breaker Type	3 Pole MCCB (4P Available as optional)
Built in Base Fuel Tank Capacity	865L
Battery	Maintenance free Lead Acid

Dimensions	Length (mm)	Width (mm)	Height (mm)	Weight (KG)
Close Type	4822	1722	2250	4747
Open Type	3500	1150	2215	3268

ENGINE SPECIFICATIONS

Engine Make Model	PERKINS 2206A-E13TAG3
No. of Cylinders	6 vertical in-line
Cycle	4 Stroke
Aspiration	Turbocharged
Cooling Method	Water cooled
Governing Type	Electronic
Governing Class	G2 - ISO 8528 Part 1
Compression Ratio	16.3:1
Displacement	12.5 L
Bore/Stroke	130 x 157 mm
Dynamic Charging Alternator	70AMP, 24V

LUBRICATION SYSTEM

Oil Filter Type	Spin-On Full Flow
Total Oil Capacity	40 L
Oil Type	API-CH-4 or ACEA E5

AIR SYSTEM

Air Filter Type	Dry Element
Combustion Air Flow (PRP)	21.3 m ³ /min
Combustion Air Flow (ESP)	23.6 m ³ /min
Max Air Filter Intake Restriction	6.4 kPa

COOLING SYSTEM

Total Coolant Capacity (L)	51.4 L
Cooling Fan Air Flow	654 m ³ / min
Radiator Fan Load	14 kW
Cooling system design	50°C
Heat Radiation to Room (PRP)	37.6 kW

Exhaust System

Muffler Type	Residential Grade
Max. Back Pressure	10 kPa
Exhaust Gas Flow (PRP/ESP)	56.6 /64.8 m ³ / min
Exhaust Gas Temperature	≤ 630 °C

Comply with Standards

ISO 3046, BS 5514, DIN 6271, NEMA-MGI, DIN EN, BS 5000, IEC 60034, IEC 60947-2

Powered By:



Silent / Closed Type

Image for illustration purposes only.

Why Sun & Energy Generator Technology (SGT)?

When you are running a business every competitive advantage counts, choosing a right Generator Set can make all the difference to bottom line.

1. Features & Benefits:

- SGT Gen set is powered by Perkins Engine , the world leader having over 85 years of innovation and excellence, with customers support in 182 countries from 3500 outlets.
- SGT Gen set is powered by Leroy Somer France Alternator, the Global number 1 in Alternators, with over 99 years of Experience, Having 120+ active patents, in over 40 countries and over 80 service centers.
- SGT Gen set is equipped with DSE controller, one of the world's top manufacturers in UK, having over 40 years of excellence, the most advanced and user friendly controller.
- Low fuel consumption, saving on fuel spend
- Compact and rugged design, saving on transport and storage cost
- Designed to occupy less space considering critical applications and cities where space is at a premium.
- Low noise and vibration, considering critical applications where noise level matters
- Easy maintenance and long service intervals , saving on maintenance cost
- Subject to rigorous tests including load acceptance, cooling, vibration and noise level prior shipment to customer.
- Simple to operate and environment friendly in worst ambient conditions
- Equipped with built-in fuel tank sufficient for 8 to 10 hours of operations.
- Fully Engineering wide range of optional accessories available.

(Contd.)



Generating Set

TECHNICAL DATA SHEET

SGT450




PERKINS Engine
2206A-E13TAG3



Leroy Somer
TAL-047-A



DSE6120 MKII AUTO
START & AUTO MAINS
FAILURE CONTROL



SGT ENCLOSURE/CANOPY

Sun & Energy Solar FZCO CEO
Building Dubai Investment Park
1 Dubai, U.A.E. +971509532031
Sun & Energy

Engine Fuel System	
Recommended Fuel	Class A2 Diesel
Fuel Consumption Standby	90 L/hr
Fuel Consumption 100% PRP	81 L/hr
Fuel Consumption 75% PRP	62 L/hr
Fuel Consumption 50% PRP	42 L/hr

ALTERNATOR SPECIFICATIONS	
Alternator Make /Model	Leroy Somer TAL-047-A
AVR Model	R150
Number of Poles	4
Number of Winding Leads	6
Type of Bearing	Single Bearing
Insulation Class - Temp Rise	Cont. H - 125/40 C
Ingress Protection Rating	IP 23
Excitation System	Self Excited
Voltage Regulation	+/- 1%
Harmonic Coefficient THF	< 2%
Tel. influence TIF	< 50
Cooling air flow	0.9 m ³ / Sec

Controller Make & Model	DeepSea 612
Operation Mode	AMF
Display	Graphic Back-lit LCD (128x64) pixels
Ingress Protection Rating	IP65
Binary Inputs/Outputs	6 / 4
Analog Inputs	3
Measurement	Vac, A, Hz, kVA, kW, Vdc
Event Log	Alarms log, Hrs log
Communication	USB

Please refer to Controller Data Sheet for more details.

Enclosure Type	Acoustic & Weather Proof
Drainage	Fuel and Water Drainage Provision
Transportation	Tested Single Point Lifting Facility & Forklift Pockets
Ingress Protection	IP 23
Lifting	ISO Standard Lifting
Canopy RAL Color	RAL 9010 - Powder coated
Base frame RAL Color	RAL 9011 - Powder coated
Noise Pressure level @	75db(A)+/-3db @ 7 mt

Distributed & Serviced by:



WE MAKE YOUR POWER SOLUTIONS SUSTAINABLE



Open Type Image for illustration purposes only.

2. WARRANTY POLICY:

- Sun & Energy Generator technology products has a warranty for all prime equipment, limited to 2000 running hours or 12 months warranty & For Standby equipment, Limited to 500 running hours or 12 months warranty whichever occur first against manufacturing defect.
- Wearing parts (filters), incorrect man-made operation, Back up Genset maintenance failures are excluded from the warranty policy
- For more details please refer to <https://www.sunergysolar.ae>

3. DOCUMENTAION

Operation and Maintenance Manual, GAD, Wiring Diagram & FAT Report are Accompanied with Genset.

. OPTIONAL FEATURES

A. Engine

- Heavy-Duty Air Filter
- Coolant Heater
- Lubricant Oil Heater
- Fuel and Water Separator
- Lube Oil Rotary Pump

B. Alternator

- Anti Condensation Heater
- PMG + AVR
- Double Bearing Alternator
- RTDs For Bearing and Winding

C. Cooling System:

- 55 degree Radiator
- Remote Radiator

D. Control System:

- AMF / Parallel
- Remote Annunciators
- 4 p manual/Motorized Circuit breaker

E. Automatic Transfer Switch (ATS):

- Contractor or Breaker type ATS
- Motorized changeover type ATS

F. Start Battery:

- Nickel-cadmium battery
- Maintenance-free battery
- Battery charger and selector switch

G. Exhaust Muffler:

- Residential grade
- Critical grade
- Hospital grade

H. Available for voltages :

400/230V,480/277V,380/220V,440/254V,
416/240V,220/127V, 208/120V

Due to continuous research & product development, we reserve the right to change specification with out notice